Vertex S+

N-type i-TOPCon Monofacial Dual Glass
MONOCRYSTALLINE MODULE


PRODUCT: TSM-NEG9R.28

PRODUCT RANGE: 425-455W

455W
MAXIMUM POWER OUTPUT

0~+5W
POSITIVE POWER TOLERANCE

22.8%
MAXIMUM EFFICIENCY



Small in size, bigger on power

- Up to 455W, 22.8% module efficiency with high density interconnect technology
- Multi-busbar technology for better light trapping, lower series resistance, improved current collection and enhanced reliability
- Reduce installation cost with higher power bin and efficiency
- Boost performance in warm weather with low temperature coefficient and operating temperature

Dual-glass Design, more secure and sustainable

- Upgraded dual glass of Vertex S, less prone to micro-cracks and scratches on the back during installation
- Excellent fire rating, weather resistance, salt spray, sand dust, ammonia performance which is fully applicable in coastal, high temperature, humidity area and harsh environment


Ultra-low Degradation, longer warranty, higher output

- First-year degradation 1% and annual degradation at 0.4%
- Up to 15/25 years product warranty and 30 years power warranty

Universal solution for residential and C&I rooftops

- Easy for integration, designed for compatibility with existing mainstream inverters and diverse mounting systems
- Perfect size and low weight for handling and installation
- Most valuable solution on low load capacity rooftops (weight similar to backsheet version)
- Mechanical performance up to 5400 Pa positive load and 4000 Pa negative load

Trina Solar's Vertex Monofacial Dual Glass Performance Warranty



Comprehensive Products and System Certificates


IEC61215/IEC61730/IEC61701/IEC62716
ISO 9001: Quality Management System
ISO 14001: Environmental Management System
ISO14064: Greenhouse Gases Emissions Verification
ISO45001: Occupational Health and Safety Management System

Trinasolar

Vertex S+


N-type i-TOPCon Monofacial Dual Glass Module

DIMENSIONS OF PV MODULE(mm)




Front View

Back View




A-A




B-B

I-V CURVES OF PV MODULE(445W)



P-V CURVES OF PV MODULE(445W)



ELECTRICAL DATA (STC)

Peak Power Watts-PMAX (Wp)*	425	430	435	440	445	450	455
Power Tolerance-PMAX (W)	0 ~ +5						
Maximum Power Voltage-VMPP (V)	42.9	43.2	43.6	44.0	44.3	44.6	45.0
Maximum Power Current-IMPP (A)	9.92	9.96	9.99	10.01	10.05	10.09	10.11
Open Circuit Voltage-VOC (V)	50.9	51.4	51.8	52.2	52.6	52.9	53.4
Short Circuit Current-ISC (A)	10.56	10.59	10.64	10.67	10.71	10.74	10.77
Module Efficiency η m (%)	21.3	21.5	21.8	22.0	22.3	22.5	22.8

STC: Irrdiance 1000W/m2, Cell Temperature 25°C, Air Mass AM1.5. *Measuring tolerance: ±3%.

ELECTRICAL DATA (NOCT)

Maximum Power-PMAX (Wp)	325	329	332	336	339	343	348
Maximum Power Voltage-VMPP (V)	40.1	40.7	41.0	41.4	41.7	42.0	42.3
Maximum Power Current-IMPP (A)	8.09	8.08	8.12	8.14	8.17	8.19	8.22
Open Circuit Voltage-VOC (V)	48.3	48.7	49.1	49.5	49.9	50.2	50.6
Short Circuit Current-ISC (A)	8.51	8.54	8.58	8.60	8.63	8.66	8.68

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

MECHANICAL DATA

Solar Cells	N-tpye Monocrystalline
No. of cells	144 cells
Module Dimensions	1762×1134×30 mm (69.06×43.15×1.18 inches)
Weight	21.0kg (46.30 lb)
Front Glass	1.6 mm (0.06 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant material	POE/EVA
Back Glass	1.6mm(0.06 inches), Heat Strengthened Glass
Frame	30mm (1.18 inches) Anodized Aluminium Alloy, Black
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm² (0.006 inches²), Portrait: 350/280 mm(13.78/11.02 inches) Length can be customized
Connector	TS4 Plus / TS4

TEMPERATURE RATINGS

NOCT(Nominal Operating Cell Temperature)	43°C (±2°C)
Temperature Coefficient of PMAX	-0.29%/°C
Temperature Coefficient of VOC	- 0.24%/°C
Temperature Coefficient of ISC	0.04%/°C

MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC (IEC)
Max Series Fuse Rating	25A

WARRANTY

15 / 25* year Product Workmanship Warranty

30 year Power Warranty

1% first year degradation

0.4% Annual Power Attenuation

(*upon request, Please refer to product warranty for details)

PACKAGING CONFIGURATION

Modules per box: 36 pieces

Modules per 40' container: 936 pieces

Trinasolar

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

© 2024 Trina Solar Co.,Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.

Version number: TSM_EN_2024_APAC_A

www.trinasolar.com